2024 Pre Tech Form Revised 04/04/2024 This form must be submitted to CKNA Tech Officials prior to entering the track for any scored session.

W.	Failure to complete this form will result in disqualification in acceptance by CKNA Officials.	any session completed prior to it's	mber:
Race C	lass (Please check all this chassis will compete in)		
	Kid Kart Sportsman Junior	Sr. Medium Masters	
\vdash	(US Only) (US Only)	= =	
느	(Canada Only)	Sr. Heavy Legends	
(art n	umber and registration (All boxes must be checked off)		
	The name I have written on the right side of this form matches the name that was given to registration		
	The number I have written on the right side of this form matches	Initials:	Oriver
_	the number that I registered with The number written on this form is displayed on my kart front, back,		Driver Name:
	and both sides with black text on either white or yellow backgrounds		19
	equipment (All boxes must be checked off)		
	Neck Collar: Required in all classes at CKNA events		
H	Cameras may not be externally mounted to helmet	Initials:	
H	Suit, gloves and shoes in good condition	Timelons:	
H	Rib protector mandatory for all drivers (Canada only)		
	Helmet meets current standards		
ngine	requirements (All boxes must be checked off)		
	Fuel lines secured to fittings with safety wire or zip ties		
	Clutch/Chain guard mounted to engine	Initials:	
	Catch cans functional and present for Gas and Oil	illitiais.	
afety	wire, circlip, safety clip or mechanical locking fastners (A	All boxes must be checked off)	
Steer	ing:		
	Steering wheel to hub bolts		
	Steering Shaft: hub to shaft bolt	Initials:	
	Tie rod end bolts		
	King pin bolts		
	Front hub to Spindle / Front Wheel nut		Par
	Steering column spherical bearing		ent
Brake	e system (must be adequate enough to quickly stop the kart)		Parent / Gu
	Pedal pivot to chassis		
	Actuating rod and cable ends	Initials:	ıardian Name:
	Master cylinder to chassis bolt		Nar
	Caliper to chassis bolts		ne:
	Pad retaining bolts		
	Brake hub to rotor bolts		
	Brake tether or secondary pedal rod		
	Throttle pedal		
<u>General</u>	al Requirements (All boxes must be checked off)		
	Ballast is painted a high contrast color, has kart number and is mounted with fasteners as described in the CKNA rules		
	Ballast is painted a high contrast color, has kart number and is	Initials:	
	Ballast is painted a high contrast color, has kart number and is mounted with fasteners as described in the CKNA rules	Initials:	
	Ballast is painted a high contrast color, has kart number and is mounted with fasteners as described in the CKNA rules Throttle return spring completely closes throttle Transonder mount at least 9" behind centerline of upper kingpin	Initials:	
□ □ Signat	Ballast is painted a high contrast color, has kart number and is mounted with fasteners as described in the CKNA rules Throttle return spring completely closes throttle Transonder mount at least 9" behind centerline of upper kingpin		
ignat under	Ballast is painted a high contrast color, has kart number and is mounted with fasteners as described in the CKNA rules Throttle return spring completely closes throttle Transonder mount at least 9" behind centerline of upper kingpin ure: stnd that completion of this form is in no way a guarentee of sa	afety or legality. Furthermore, I agree	
ignat under o follo	Ballast is painted a high contrast color, has kart number and is mounted with fasteners as described in the CKNA rules Throttle return spring completely closes throttle Transonder mount at least 9" behind centerline of upper kingpin	afety or legality. Furthermore, I agree	
ignat under o follo	Ballast is painted a high contrast color, has kart number and is mounted with fasteners as described in the CKNA rules Throttle return spring completely closes throttle Transonder mount at least 9" behind centerline of upper kingpin ure: stnd that completion of this form is in no way a guarentee of saw the rules and rulings made by CKNA as laid out in their free r	afety or legality. Furthermore, I agree	
ignat under o follo	Ballast is painted a high contrast color, has kart number and is mounted with fasteners as described in the CKNA rules Throttle return spring completely closes throttle Transonder mount at least 9" behind centerline of upper kingpin ure: stnd that completion of this form is in no way a guarentee of saw the rules and rulings made by CKNA as laid out in their free r	afety or legality. Furthermore, I agree	